

**24*GE + 8*GF + 4*TF
Managed Ethernet Switch
DES-46S12MG-HD**



**Elevate Your Connectivity With
Our Latest Network Switches**



DES-46S12MG-HD**24*GE + 8*GF + 4*TF Managed Ethernet Switch**

- ☆ 24*10/100/1000M RJ45 + 8*100/1000M SFP slot + 4*1/2.5/10G SFP+ Fiber Slot Uplink Managed Ethernet Switch,
- ☆ Comply with IEEE 802.3, IEEE 802.3u, IEEE802.3ab, IEEE802.3z standards;
- ☆ Support QOS, STP/RSTP, IGMP, DHCP, SNMP, WEB, VLAN, ERPS etc.;
- ☆ Support connection with IP Cameras and wireless AP.
- ☆ Plug and play, no need more configuration.
- ☆ Low power consumption design. Low power consumption design. Energy-saving and green. Max total power consumption < 15W.

Introduction;

The DES-46S12MG-HD is a 10G uplink managed ethernet switch. It has 24*10/100/1000Base-T RJ45 ports and 8*100/1000Base-X SFP fiber slot ports and 4*1/2.5/10G SFP+ fiber slot ports. It is suitable for hotel, campus, factory dormitory and small and medium-sized enterprise. The DES-46S12MG-HD has the L2+ full network management function, supports IPV4/IPV6 management, supports static route full line rate forwarding, supports complete security protection mechanism, complete ACL/QoS policy and rich VLAN functions, and is easy to manage and maintain. Supports multiple network redundancy protocols STP/RSTP/MSTP (<50ms) and (ITU-T G.8032) ERPS to improve link backup and network reliability. When one-way network fails, communication can be quickly restored to ensure important Uninterrupted communication for applications.

Technical Specifications;

Model	DES-46S12MG-HD
Interface	24*10/100/1000Base-T/TX RJ45 ports (Data) 8*100/1000Base-X SFP fiber slot ports (Data) 4*1/2.5/10G uplink SFP+ fiber slot ports (Data) 1*Console RS232 port (115200, N,8,1)
Network Protocol	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u 100Base-TX; IEEE802.3ab 1000Base-T; IEEE802.3z 1000Base-X; IEEE802.3ae 10GBase-SR/LR; IEEE802.3x
Network	L2+
Ethernet port	10/100/1000Base-T(X), Auto-Detection, Full/half duplex MDI/MDI-X self-adaption
Fiber port Feature	1G/2.5G/10G SFP fiber interface (Fiber module is not included, need to order separately, module optios include single/multi-mode, single/dual fiber, LC)
Forwarding Mode	Store and Forward
Switching Capacity	144Gbps (non-blocking)
Forwarding Rate	107.14Mpps
MAC	32K
Buffer Memory	32M
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP (≤100 meter) 100BASE-TX: Cat5 or later UTP (≤100 meter) 1000BASE-T: Cat5e or later UTP (≤100 meter)
Optical Cable	Multi-mode:850nm 0~300M(10G) ,850nm 0~500M (1.25G); Single-mode:1310nm 0~40KM,1550nm 0~120KM.
Power Supply	Built-in power supply, AC 100~220V 50-60Hz
Reset Switch	Yes, One-button factory reset
Operation TEMP/Humidity	-20~+55°C;5%~90% RH Non condensing
Storage TEMP /Humidity	40~+80°C;5%~95% RH Non condensing
LED Indicator	PWR (green); system indicator's SYS (green); Network Indicator: Link/Act (yellow); SFP Indicator: L/A (green); PoE Indicator: PoE (green)

Technical Specifications;

Model	DES-46S12MG-HD
Protection	IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge IEC61000-4-5(Lightning protection/Surge): Power:CM±4kV/DM±2kV; Port: ±4kV
Dimension	440*290*44.5mm
Net /Gross Weight	<4.6kg / <5.5kg
Lightning protection / protection level	IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge IEC61000-4-5(Lightning protection/Surge): Power:CM±4kV/DM±2kV; Port: ±4kV IP30
Installation	Desktop, 19-inch 1U cabinet
Certification	CCC; CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;
Managed Feature	
Interface	IEEE802.3x flow control (full duplex) Broadcast storm suppression for port rate support speed limit for incoming and offline message traffic, with a minimum particle size of 64Kbps. Temperature protection setting Energy saving configuration of port EEE Ethernet
VLAN	Support port based VLAN (4K), IEEE802.1q Support protocol based VLAN Support Access, Trunk, Hybrid three types of port configuration Support QinQ configuration
Port Aggregation	Support LACP Support static polymerization Support the largest 8 aggregation groups, each aggregation group supports 8 ports.
Image	Bi-directional traffic mirroring supporting the basic port

Lorem ipsum

Technical Specifications;

Model	DES-46S12MG-HD
Spanning Tree	STP (IEEE802.1d) RSTP (IEEE802.1w) MSTP (IEEE802.1s)
Industrial Ring Network Protocol	Support G.8032 (ERPS), support 255 loops at most, and supports 1024 devices per ring. The self-healing time of the ring network is less than 20ms
DHCP	Support DHCP Client Support DHCP Snooping Support DHCP Serve Support DHCP Relay
Industrial Ring Network Protocol	Support G.8032 (ERPS), support 255 loops at most, and supports 1024 devices per ring. The self healing time of the ring network is less than 20ms
Multicast	Support IGMP Snooping V1/V2 and support 1024 multicast groups at most. Support the user's quick departure mechanism Support MLD Snooping V1/V2 Support multicast VLAN
QoS	Diff-Serv QoS Each port supports 8 output queues Support 802.1p/DSCP priority mapping Support queue scheduling mechanism (SP, WRR, SP+WRR) priority tag Mark/Remark stream based packet filtering Support for stream-based redirection Support flow-based speed limit
ACL	Support L2 to L4 packet filtering function, can match the first 80 bytes of the message, provide based on the source MAC address, destination MAC address, source IP address, destination IP address, IP protocol type, TCP/UDP port, TCP/UDP port range, VLAN and other definition ACL. Support ACL based on port and VLAN
Safety Characteristics	Support user grading management and password protection Support IEEE802.1X authentication / centralized MAC address authentication Support AAA&RADIUS authentication Support the number of MAC address learning restrictions Support MAC address black hole Support SSH 2 to provide secure passwords for user login. Support SSL to ensure data transmission security Support port isolation Support the speed limit function of ARP message Support IP source address protection Support ARP intrusion detection function

DATASHEET

Technical Specifications;

Model	DES-46S12MG-HD
	<ul style="list-style-type: none"> Support against DoS attacks Support port broadcast message suppression Support host data backup mechanism Binding capabilities of IP+MAC+VLAN+ ports
Management and Maintenance	<ul style="list-style-type: none"> Support Console/AUX Modem/Telnet/SSH2.0 CLI command line configuration Support WEB network management (HTTPS) Support FTP, TFTP, Xmodem, SFTP file download management Support SNMP V1/V2C/V3 Support one bond reduction Support NTP clock Support system work log Support Ping detection Support cable state detection Support CPU instant utilization status view Support link layer discovery protocol LLDP Support NMS intelligent management center
System Requirements	<ul style="list-style-type: none"> Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42 or higher, Microsoft Internet Explorer10 or later; Cat5e or later Ethernet cable; TCP/ IP, network adapter and network operating system (Microsoft Windows, Linux or Mac OS X) installed on on every computer in the network.

Packaging List

CONTENT	QTY	UNIT
36 ports managed Ethernet Switch with 4*10G SFP (DES-46S12MG-HD)	1	SET
Hanging Ear	1	PAIR
User Guide	1	PC
Warranty Card	1	PC